




Aprisa SR+

SMART, SECURE POINT-TO-MULTIPOINT RADIO VHF, 220 MHz, and UHF licensed bands



Smart, secure, industry-leading speed licensed point-to-multipoint SCADA communications for industrial monitoring and control for the electricity, water, oil and gas industries – now with 256 QAM

- **High capacity:** to meet the growing number of data-intensive applications in the SCADA environment, the Aprisa SR+ provides data rates of up to 512 kbit/s half duplex / 1,024 kbit/s full duplex in 100 kHz licensed channels.
- **Secure:** with its defense in depth approach, including AES encryption, authentication, address filtering and user access control including RADIUS, the Aprisa SR+ protects against vulnerabilities and malicious attacks.
- **Future-proof:** the Aprisa SR+ supports dual serial and dual Ethernet ports in a single, compact form factor, designed to cryptographically secure legacy serial, protect existing device investment, and enable new applications. Old and new application protocols can be run side by side.
- **Advanced L2 / L3 capabilities:** selectable L2 bridge, L3 router, or advanced gateway router combination L2/L3 modes with VLAN, QoS, NAT, and filtering attributes to maximize capacity in constrained bandwidth and prioritize mission critical traffic while meeting tough security and IP network policy imperatives.
- **Adaptable:** the Aprisa SR+ integrates into a range of network topologies, with each unit configurable as a master station, repeater or remote station; connect multiple RTUs / PLCs to a single radio.
- **Flexible interfaces:** the data interfaces can be configured for serial or Ethernet operation; a range of options are supported, including two serial and two Ethernet, one serial and three Ethernet, or four Ethernet ports. Support for NMEA GPS receiver option.
- **Link efficiency:** Adaptive Coding and Modulation (ACM) and forward error correction maintains the integrity of the wireless connection while an effective channel access scheme and IP routing ensures efficient transfer of data across the Aprisa SR+ network. Automatic Transmit Power Control maintains the minimum transmit power required for effective communications enhancing both frequency reuse and power savings. Advanced payload and Ethernet / IP / TCP / UDP header compression.
- **Reliable and robust:** the Aprisa SR+ requires no manual component tuning and maintains its performance over a wide temperature range using full specification industrially rated components and shared Aprisa family heritage.
- **Easily managed:** an easy to use GUI supports local element management via HTTPS and remote element management over the air and SNMP support allows network-wide monitoring and control via a variety of supported third party network management systems.



The Aprisa SR+ in brief

- VHF, 220 MHz, and UHF licensed bands
- RS-232 and IEEE 802.3 with multiple port options
- Software selectable 12.5 kHz, 20 kHz, 25 kHz, 50 kHz, and 100 kHz (note 2) channel sizes (frequency band dependent)
- Full and half duplex operation, single or dual frequency
- Data rates of up to 512 kbit/s half duplex / 1024 kbit/s full duplex
- 256, 192 or 128 bit AES encryption
- AES-CCM to NIST SP 800-38C
- Adaptive Coding and Modulation: QPSK to 256 QAM
- Automatic Transmit Power Control: reduces interference in large networks, improves power savings
- Advanced forward error correction
- Ethernet and IP / TCP / UDP header compression (ROHC) and payload compression
- Software selectable dual / single antenna port operation
- Transparent to all common SCADA protocols
- Dedicated alarm port and optional GPS for radio coordinates
- Protected station and remote station options
- Power optimized option
- Layer 2 bridge (VLAN aware), layer 3 router, and advanced gateway router combination L2/ L3 modes
- VLAN tagging and Q-in-Q
- Flexible QoS priority enforcement – by port or traffic type, VLAN, PCP/DSCP, rule including SMAC/DMAC, IP address and IP protocol, and EtherType
- L2 / L3 / L4 filtering
- Substation hardened to IEEE 1613 class 2 and IEC 61850-3
- 30 kV ESD antenna protection
- Class 1, Division 2 for hazardous protection
- -40 to +70 °C operational temperature without fans
- 210 mm (W) x 130 mm (D) x 41.5 mm (H)
- Complies with EU RED (2014/53/EU)

Aprisa SR+ applications

- Electricity grid: distribution automation control and protection in MV / HV distribution / transmission
- Smart grid, DA, DFA, DER, cap bank control
- Oil & Gas: production metering, lift pump automation
- AMI / AMR: high density data concentrator backhaul
- Renewables: wind farm, tidal, hydro automation
- Water and wastewater: flow, level, pressure modulation automation and pump status

GENERAL							
NETWORK TOPOLOGY	Point-to-multipoint (PMP), Base, Remote, Repeater						
NETWORK INTEGRATION	Serial and Ethernet (router or bridge mode)						
PROTOCOLS							
ETHERNET	IEEE 802.3, 802.1d/q/p						
SERIAL	Legacy RS-232 transport						
WIRELESS	Proprietary						
SCADA	Transparent to user traffic; e.g. Modbus, IEC 60870-5-101/104, DNP3 or similar						
RADIO							
FREQUENCY RANGE	FREQ BAND	TUNING RANGE	TUNE STEP				
	135 MHz	135 – 175 MHz	0.625 kHz				
	(Note 2) 220 MHz	215 – 240 MHz	0.625 kHz				
	320 MHz	320 – 400 MHz	6.25 kHz				
	400 MHz	400 – 470 MHz	1.25 kHz				
	450 MHz	450 – 520 MHz	6.25 kHz				
CHANNEL SIZE	12.5 kHz, 20 kHz, 25 kHz, 50 kHz and 100 kHz (note 2) software selectable						
DUPLEX	Single frequency half-duplex Dual frequency half-duplex Dual frequency full-duplex						
FREQUENCY STABILITY	± 0.5 ppm						
FREQUENCY AGING	< 1 ppm / annum						
TRANSMITTER							
MAX PEAK ENVELOPE POWER (PEP)	10.0 W (+40 dBm)						
AVERAGE POWER OUTPUT	256 QAM 0.01 – 2.0 W (+10 to +33 dBm, in 1 dB steps)						
	64 QAM 0.01 – 2.5 W (+10 to +34 dBm, in 1 dB steps)						
	16 QAM 0.01 – 3.2 W (+10 to +35 dBm, in 1 dB steps)						
	QPSK 0.01 – 5.0 W (+10 to +37 dBm, in 1 dB steps)						
	(Note 2) 4-CPFSK 0.01 – 10.0 W (+10 to +40 dBm, in 1 dB steps)						
ADJACENT CHANNEL POWER	< –60 dBc						
TRANSIENT ADJACENT CHANNEL POWER	< –60 dBc						
SPURIOUS EMISSIONS	< –37 dBm						
ATTACK TIME	< 1.5 ms						
RELEASE TIME	< 0.5 ms						
DATA TURNAROUND TIME	< 2 ms						
EMISSION DESIGNATOR SUFFIX	QPSK G1D, QAM D1D						
RECEIVER							
		12.5 kHz	20 kHz	25 kHz	50 kHz	100 kHz	
SENSITIVITY (BER < 10 ⁻⁶)	max coded	256 QAM	–97 dBm	–93 dBm	–93 dBm	–90 dBm	–87 dBm
	max coded	64 QAM	–103 dBm	–99 dBm	–99 dBm	–96 dBm	–93 dBm
	max coded	16 QAM	–110 dBm	–107 dBm	–107 dBm	–104 dBm	–101 dBm
	max coded	QPSK	–115 dBm	–112 dBm	–112 dBm	–109 dBm	–106 dBm
	min coded	4-CPFSK	–113 dBm	–110 dBm	–110 dBm	–107 dBm	–104 dBm
ADJACENT CHANNEL SELECTIVITY		> –47 dBm	> –37 dBm	> –37 dBm	> –37 dBm	> –37 dBm	
		(Note 1) [> 48 dB]	[> 58 dB]	[> 58 dB]	[> 58 dB]	[> 58 dB]	
CO-CHANNEL REJECTION max coded QPSK		> –10 dB					
CO-CHANNEL REJECTION max coded 256 QAM		> –26 dB					
INTERMODULATION RESPONSE REJECTION		> –35 dBm [≥ 60 dB Note 1]					
BLOCKING OR DESENSITISATION		> –17 dBm [≥ 78 dB Note 1]					
SPURIOUS RESPONSE REJECTION		> –32 dBm [≥ 63 dB Note 1]					
MODEM							
		12.5 kHz	20 kHz	25 kHz	50 kHz	100 kHz	
GROSS DATA RATE	256 QAM	80 kbit/s	112 kbit/s	160 kbit/s	288 kbit/s	512 kbit/s	
	64 QAM	60 kbit/s	84 kbit/s	120 kbit/s	216 kbit/s	384 kbit/s	
	16 QAM	40 kbit/s	56 kbit/s	80 kbit/s	144 kbit/s	256 kbit/s	
	QPSK	20 kbit/s	28 kbit/s	40 kbit/s	72 kbit/s	128 kbit/s	
	4-CPFSK	9.6 kbit/s	9.6 kbit/s	19.2 kbit/s	38.4 kbit/s	76.8 kbit/s	
FORWARD ERROR CORRECTION		Variable length concatenated Reed Solomon plus convolutional code					
ADAPTIVE BURST SUPPORT		Adaptive Coding and Modulation					

SECURITY	
DATA ENCRYPTION	256, 192 or 128 bit AES
DATA AUTHENTICATION	CCM
INTERFACES	
ETHERNET	2, 3 or 4 port RJ45 10/100Base-T switch (specified at order)
SERIAL	2, 1 or 0 port RJ45 RS-232 (specified at order) Additional RS-232 / RS-485 port via USB converter (optional)
MANAGEMENT	1 x USB micro type B (device port) 1 x USB standard type A (host port) 1 x Alarm port RJ45
ANTENNA	2 x TNC 50 ohm female Software selectable single or dual port operation
LEDs	Status: OK, MODE, AUX, TX, RX Diagnostics: RSSI, traffic port status
TEST BUTTON	Toggles LEDs between diagnostics / status
PRODUCT OPTIONS	
DATA PORT CONFIGURATION	2 x Ethernet ports + 2 serial ports 3 x Ethernet ports + 1 serial port 4 x Ethernet ports
POWER OPTIMIZED	Providing optimized power and sleep mode
PROTECTED STATION	Providing hot-swappable / hot-standby redundant hardware switching (13.8 VDC or 48 VDC)
GPS RECEIVER	Support for NMEA GPS receiver with radio coordinates
POWER	
INPUT VOLTAGE	10 – 30 VDC (13.8 V nominal)
RECEIVE	All bands except 320 MHz < 3 W in active receive state < 2 W in idle receive state, < 0.5 W in sleep mode
	320 MHz < 7 W
TRANSMIT	135 and 220 MHz < 26 W 400 and 450 MHz < 28 W 320 MHz < 35 W
MECHANICAL	
DIMENSIONS	210 mm (W) x 130 mm (D) x 41.5 mm (H)
WEIGHT	1.25 kg
MOUNTING	Wall, Rack or DIN rail
ENVIRONMENTAL	
OPERATING TEMPERATURE	–40 to +70 °C
HUMIDITY	Maximum 95 % non-condensing
MANAGEMENT & DIAGNOSTICS	
LOCAL ELEMENT	SSH and HTTP/S web servers with full control / diagnostics Partial diagnostics via LEDs and test button Software upgrade from PC or USB flash drive
REMOTE ELEMENT	SSH and HTTP/S over-the-air remote element management with control / diagnostics Network software upgrade over-the-air
NETWORK	SNMPv2 and SNMPv3 security support for integration with external network management systems
COMPLIANCE	
RED COMPLIANCE	Tested to Radio Equipment Directive 2014/53/EU (note 3)
RF	12.5 kHz EN 300 113 25 kHz, 50 kHz and 100 kHz EN 302 561
EMC	EN 301 489-1 and 5
SAFETY	EN 60950 Class 1 division 2 for hazardous locations
ENVIRONMENTAL	ETS 300 019 Class 3.4, Ingress Protection IP51 Substation hardened to IEEE 1613 class 2 and IEC 61850-3

Notes:

- The receiver figures are shown in typical fixed interference dBm values and dB values [in brackets] relative to the sensitivity. Relative values are given for QPSK modulation and max coded FEC. Refer to the Aprisa SR+ User Manual for a complete list of modulation and coding levels.
- Please consult 4RF for availability.
- 100 kHz subject to EU RED verification

ABOUT 4RF

Operating in more than 150 countries, 4RF provides radio communications equipment for critical infrastructure applications. Customers include utilities, oil and gas companies, transport companies, telecommunications operators, international aid organisations, public safety, military and security organisations. 4RF point-to-point and point-to-multipoint products are optimized for performance in harsh climates and difficult terrain, supporting IP, legacy analogue, serial data applications.

Copyright © 2020 4RF Limited. All rights reserved. This document is protected by copyright belonging to 4RF Limited and may not be reproduced or republished in whole or part in any form without the prior written consent of 4RF Limited. While every precaution has been taken in the preparation of this literature, 4RF Limited assumes no liability for errors or omissions, or from any damages resulting from the use of this information. The contents and product specifications within it are subject to revision due to ongoing product improvements and may change without notice. Aprisa and the 4RF logo are trademarks of 4RF Limited.



For more information please contact
EMAIL sales@4rf.com
URL www.4rf.com