

New Modem 2 performance
New Aprisa SR+ mixed
network interoperation


Aprisa SR

SMART, SECURE POINT-TO-MULTIPOINT RADIO VHF, 220 MHz, and UHF licensed bands



Smart, secure, point-to-multipoint SCADA communications for oil, gas and utility monitoring and control

- **Secure:** with its defense in depth approach, including AES encryption, authentication, address filtering and user access control including RADIUS, the Aprisa SR protects against vulnerabilities and malicious attacks.
- **Future-proof:** the Aprisa SR supports dual serial and dual Ethernet ports in a single, compact form factor, designed to cryptographically secure legacy serial, protect existing device investment, and enable new applications. Old and new application protocols can be run side by side. New Modem 2 firmware allows mixed network operation with Aprisa SR+ at full speed – facilitating a seamless upgrade to 256 QAM operation.
- **Advanced L2 / L3 capabilities:** selectable L2 bridge, L3 router, or advanced gateway router combination L2 / L3 modes with VLAN, QoS, NAT, and filtering attributes to maximize capacity in constrained bandwidth and prioritize mission critical traffic while meeting tough security and IP network policy imperatives.
- **Flexible:** the Aprisa SR integrates into a range of network topologies, with each unit configurable as a base station, repeater or remote unit. Support for NMEA GPS receiver option.
- **Link efficiency:** forward error correction maintains the integrity of the wireless connection while an effective channel access scheme and IP routing ensures efficient transfer of data across the Aprisa SR network. Automatic Transmit Power Control maintains the minimum transmit power required for effective communications enhancing both frequency reuse and power savings. Advanced payload and Ethernet / IP / TCP / UDP header compression.
- **Reliable and robust:** the Aprisa SR requires no manual component tuning and maintains its performance over a wide temperature range using full specification industrially rated components and shared Aprisa family heritage. Modem 2 performance brings new levels of robust QPSK demodulation and large network improvements.
- **Easily managed:** an easy to use GUI supports local element management via HTTPS and remote element management over the air and SNMP support allows network-wide monitoring and control via a variety of supported third party network management systems.



The Aprisa SR in brief

- VHF, 220 MHz, and UHF licensed bands
- RS-232 and IEEE 802.3 protocols
- Software selectable 12.5 kHz, 15 kHz, 25 kHz, 30 kHz, 50 kHz, and 100 kHz (note 2) channel sizes (frequency band dependent)
- Data rates of up to 128 kbit/s
- QPSK modulation with adaptive coding
- Mixed network operation with the Aprisa SR+
- Automatic Transmit Power Control: reduces interference in large networks, improves power savings
- Selectable error correction of min, max or no FEC
- AES-CCM to NIST SP 800-38C
- Ethernet and IP / TCP / UDP header compression (ROHC) and payload compression
- Software selectable dual / single antenna port operation
- Transparent to all common SCADA protocols
- Dedicated alarm port
- Optional USB connected GPS receiver
- Power optimized option
- Layer 2 bridge (VLAN aware), layer 3 router, and advanced gateway router combination L2/ L3 modes
- VLAN tagging and Q-in-Q
- Flexible QoS priority enforcement – by port or traffic type, VLAN, PCP/DSCP, rule including SMAC/DMAC, IP address and IP protocol, and EtherType
- L2 / L3 / L4 filtering
- MEMS accelerometer motion sensing anti-tamper option
- Substation hardened to IEEE 1613 class 2 and IEC 61850-3
- 30 kV ESD antenna protection
- Class 1, Division 2 for hazardous protection
- -40 to +70 °C operational temperature without fans
- 210 mm (W) x 130 mm (D) x 41.5 mm (H)
- Complies with EU RED (2014/53/EU)

Aprisa SR applications

- Offshore rigs and onshore pump jacks
- Transmission pipelines
- Electricity generation plants and turbines
- Power storage and distribution
- Water and waste processing plants

| GENERAL | | | | | | |
|---|--|--|-----------|-----------|-----------|------------|
| NETWORK TOPOLOGY | Point-to-multipoint (PMP), Base, Remote, Repeater | | | | | |
| NETWORK INTEGRATION | Serial and Ethernet (router or bridge mode) | | | | | |
| PROTOCOLS | | | | | | |
| ETHERNET | IEEE 802.3, 802.1d/q/p | | | | | |
| SERIAL | Legacy RS-232 transport | | | | | |
| WIRELESS | Proprietary | | | | | |
| SCADA | Transparent to user traffic; e.g. Modbus, IEC 60870-5-101/104, DNP3 or similar | | | | | |
| RADIO | | | | | | |
| FREQUENCY RANGE | FREQ BAND | TUNING RANGE | TUNE STEP | | | |
| | 135 MHz | 135 – 175 MHz | 0.625 kHz | | | |
| | (Note 2) 220 MHz | 215 – 240 MHz | 0.625 kHz | | | |
| | 320 MHz | 320 – 400 MHz | 6.25 kHz | | | |
| | 400 MHz | 400 – 470 MHz | 1.25 kHz | | | |
| | 450 MHz | 450 – 520 MHz | 6.25 kHz | | | |
| CHANNEL SIZE | 12.5 kHz, 20 kHz, 25 kHz, 50 kHz and 100 kHz (note 2) software selectable | | | | | |
| DUPLEX | Single frequency half-duplex Dual frequency half-duplex Half duplex remote with SR+ full duplex base station | | | | | |
| FREQUENCY STABILITY | ± 0.5 ppm | | | | | |
| FREQUENCY AGING | < 1 ppm / annum | | | | | |
| TRANSMITTER | | | | | | |
| MAX PEAK ENVELOPE POWER (PEP) | 10.0 W (+40 dBm) | | | | | |
| AVERAGE POWER OUTPUT | QPSK | 0.01 – 5.0 W (+10 to +37 dBm, in 1 dB steps) | | | | |
| ADJACENT CHANNEL POWER | < –60 dBc | | | | | |
| TRANSIENT ADJACENT CHANNEL POWER | < –60 dBc | | | | | |
| SPURIOUS EMISSIONS | < –37 dBm | | | | | |
| ATTACK TIME | < 1.5 ms | | | | | |
| RELEASE TIME | < 0.5 ms | | | | | |
| DATA TURNAROUND TIME | < 2 ms | | | | | |
| EMISSION DESIGNATOR SUFFIX | QPSK G1D | | | | | |
| RECEIVER | | | | | | |
| | | 12.5 kHz | 20 kHz | 25 kHz | 50 kHz | 100 kHz |
| SENSITIVITY (BER < 10 ⁻⁹) max coded | QPSK | –115 dBm | –112 dBm | –112 dBm | –109 dBm | –106 dBm |
| ADJACENT CHANNEL SELECTIVITY | | > –47 dBm | > –37 dBm | > –37 dBm | > –37 dBm | > –37 dBm |
| | (Note 1) | [> 48 dB] | [> 58 dB] | [> 58 dB] | [> 58 dB] | [> 58 dB] |
| CO-CHANNEL REJECTION max coded | QPSK | > –10 dB | | | | |
| INTERMODULATION RESPONSE REJECTION | | > –35 dBm [> 60 dB Note 1] | | | | |
| BLOCKING OR DESENSITISATION | | > –17 dBm [> 78 dB Note 1] | | | | |
| SPURIOUS RESPONSE REJECTION | | > –32 dBm [> 63 dB Note 1] | | | | |
| MODEM | | | | | | |
| | | 12.5 kHz | 20 kHz | 25 kHz | 50 kHz | 100 kHz |
| GROSS DATA RATE | QPSK | 20 kbit/s | 28 kbit/s | 40 kbit/s | 72 kbit/s | 128 kbit/s |
| FORWARD ERROR CORRECTION | Variable length concatenated Reed Solomon plus convolutional code | | | | | |
| ADAPTIVE BURST SUPPORT | Adaptive Coding | | | | | |
| SECURITY | | | | | | |
| DATA ENCRYPTION | 256, 192 or 128 bit AES | | | | | |
| DATA AUTHENTICATION | CCM | | | | | |

| INTERFACES | |
|--------------------------------------|---|
| ETHERNET PORTS | 2 port RJ45 10/100Base-T auto-neg MDI/MDIX |
| SERIAL PORTS | 2 port RJ45 RS-232 Additional RS-232 / RS-485 port via USB converter (optional) |
| GPS RECEIVER | Support for optional USB connected GPS receiver |
| MANAGEMENT | 1 x USB micro type B (device port) 1 x USB standard type A (host port) 1 x Alarm port RJ45 |
| ANTENNA | 2 x TNC 50 ohm female Software selectable single or dual port operation |
| LEDs | Status: OK, MODE, AUX, TX, RX Diagnostics: RSSI, traffic port status |
| TEST BUTTON | Toggles LEDs between diagnostics / status |
| PRODUCT OPTIONS (specified at order) | |
| ANTENNA PORT OPTION | Single antenna port or dual antenna port |
| POWER | |
| INPUT VOLTAGE | 10 – 30 VDC |
| RECEIVE | All bands except 320 MHz < 3 W in active receive state < 2 W in idle receive state, < 0.5 W in sleep mode |
| | 320 MHz < 7 W |
| TRANSMIT | 135 and 220 MHz < 26 W 400 and 450 MHz < 28 W 320 MHz < 35 W |
| MECHANICAL | |
| DIMENSIONS | 210 mm (W) x 130 mm (D) x 41.5 mm (H) |
| WEIGHT | 1.25 kg |
| MOUNTING | Wall, Rack or DIN rail |
| ENVIRONMENTAL | |
| OPERATING TEMPERATURE | –40 to +70 °C |
| HUMIDITY | Maximum 95 % non-condensing |
| MANAGEMENT & DIAGNOSTICS | |
| LOCAL ELEMENT | SSH and HTTP/S web servers with full control / diagnostics Partial diagnostics via LEDs and test button Software upgrade from PC or USB flash drive |
| REMOTE ELEMENT | SSH and HTTP/S over-the-air remote element management with control / diagnostics Network software upgrade over-the-air |
| NETWORK | SNMPv2 and SNMPv3 security support for integration with external network management systems |
| COMPLIANCE | |
| RED COMPLIANCE | Tested to Radio Equipment Directive 2014/53/EU (note 3) |
| RF | 12.5 kHz EN 300 113 25 kHz, 50 kHz and 100 kHz EN 302 561 400 MHz 12.5 kHz and 25 kHz EN 300 220-2 V3.2.1 for Ofcom IR2030/2/6 or IR2030/2/7 |
| EMC | EN 301 489-1 and 5 |
| SAFETY | EN 60950 Class 1 division 2 for hazardous locations |
| ENVIRONMENTAL | ETS 300 019 Class 3.4, Ingress Protection IP51 Substation hardened to IEEE 1613 class 2 and IEC 61850-3 |

Notes:

- The receiver figures are shown in typical fixed interference dBm values and dB values (in brackets) relative to the sensitivity. Relative values are given for QPSK modulation and max coded FEC. Refer to the Aprisa New SR User Manual for a complete list of modulation and coding levels.
- Please consult 4RF for availability.
- 100 kHz subject to EU RED verification.

ABOUT 4RF

Operating in more than 150 countries, 4RF provides radio communications equipment for critical infrastructure applications. Customers include utilities, oil and gas companies, transport companies, telecommunications operators, international aid organisations, public safety, military and security organisations. 4RF point-to-point and point-to-multipoint products are optimized for performance in harsh climates and difficult terrain, supporting IP, legacy analogue, serial data applications.

Copyright © 2022 4RF Limited. All rights reserved. This document is protected by copyright belonging to 4RF Limited and may not be reproduced or republished in whole or part in any form without the prior written consent of 4RF Limited. While every precaution has been taken in the preparation of this literature, 4RF Limited assumes no liability for errors or omissions, or from any damages resulting from the use of this information. The contents and product specifications within it are subject to revision due to ongoing product improvements and may change without notice. Aprisa and the 4RF logo are trademarks of 4RF Limited.



For more information please contact
EMAIL sales@4rf.com
URL www.4rf.com

Version 2.8.0